

2200 SERIES

FLEX-WING ROTARY CUTTERS

2215



The 2215 Medium-Plus Duty Flex-Wing

The Bush Hog® model 2215 Flex-Wing rotary cutter is designed to cut grass, weeds, and brush up to 3 ½" in diameter. It is recommended for use in pasture maintenance, crop shredding, and roadside maintenance. With maintenance friendly features such as EZ clean decks, EZ-Lube drivelines and Bush Hog® tough durability, the 2215 is another Flex-Wing example of Bush Hog® Performance You Can Count On.

The 2215 comes standard with Perma-Level Hitch and choice of 540 or 1000 RPM CV input drivelines, with or without Deck Ring, Center Dual or Walking Tandem Axles, Wing Single, Dual, or Walking Tandem Axles, 6 Selections of Tires, and Single or Double Row Safety Chains.



Each axle arm on the center and wings has a spring cushion to absorb the shock loads near the wheel.

2215 Model Features

- **Axle spindles** are in halves for quick and economical service.
- **Center section blades** closely align with center section wheels for more even cutting of ditch bottoms.
- **Grease fittings and steel bushings** at axle pivot points for extended life.
- **Wing free float** 22° down and 45° up without moving the hydraulic cylinder, extending cylinder life.
- **Optional distribution baffles** distribute clippings more evenly across the width of the cutter.
- **Improved wing design** results in a smooth top and underside.
- **Patented oil sight windows** in cutting gearboxes allows for quick and easy visual inspection of oil levels

KEY DIFFERENCES BETWEEN 2215 AND 1815

MODELS:	2215	1815
Splitter Gearbox HP	250	160
Cutting Gearbox HP	210	130
Cutting Capacity	3 ½"	2 ½"
Blade Tip Speed	16,286 FPM	15,000 FPM
Main Axle Tubes	Center: 4" x 4" x 5/16" Wall Wings: 4" x 4" x 5/16" Wall	Center: 4" Round x 5/16" Wall Wings: 4" Round x 5/16" Wall
Axle Sleeves	Center: 5 ½" x 4 ¼" x 1/4" Wall Wings: 5 ½" x 4 ¼" x 1/4" Wall	5 ½" Channel x 1/4" Wall
Axle Suspension	Springs on Each Axle Arm	Rubber Isolators on Center Axle Arms



Bush Hog's EZ-Lube drivelines are quick and easy to service. All grease fittings on the PTO CV drivelines and wing drivelines closely align for quick location of grease points.

2215 FLEX-WING ROTARY CUTTER SPECIFICATIONS

Transport Height*	7' 3"	Blade Overlap	6"
Transport Width**	8' 2"	Blade Tip Speed	16,286 fpm (540 rpm); 16,000 fpm (1000 rpm)
Cutting Width	15'	Wing Cutting Angles	22° Down to 45° Up
Axle Suspension	Cushioned Springs at Each Wheel	Center Hydraulic Lift	Standard
Cutting Height	1 ½" - 14"	Wing Hydraulic Lift	Standard
Cutting Capacity	3 ½" Diameter	Axle Tube Pivots	Greaseable Bushings
Hitch	Self-Leveling Perma-Level®	Axle Arm Pivots	Greaseable
Approx. Tongue Weight	1,800 lb.	Wing Adjustment	Greaseable Turnbuckles
Deck Thickness	10 Gauge	Wheels	Choice of Laminated, Pneumatic Aircraft, or Foam-Filled Aircraft
Side Bands	1/4" x 13 ½"	Minimum Tractor PTO HP	60 (PTO)
Gearbox	250 hp† Splitter Gearbox, 210 hp† Cutting Gearboxes	Grass Baffles	Optional
Drivelines	Main: ASAE Cat. 6 (540); ASAE Cat. 5 (1,000) Wings: ASAE Cat. 4	Jack Stand	Standard
Driveline Protection	(3) Multi-Plate Slip Clutch	Safety Tow Chain	Standard
Blade Holder	7 Gauge Round Pan	Safety Deflectors	Single or Double Row Chains
Blades	1/2" x 4" Parallel Uplift	Warranty	10-Year Gearbox Limited Warranty 1-Year Machine Limited Warranty

*Measured at maximum transport height.
**Measured at outside of wing skirts.
†Gearbox rating based on field performance.